



ASYMMETRIC

S E R I

KAPILARIMIZIN KANATLARI

- 1,2mm x 2 plaka yekpare çelikten CNC makinalarımızla pres-büküm ve ezme yapılarak bir bütün olarak imal edilir. Kanat imalatında Parça çelik veya kaynak gibi zayıflatıcı hiçbir teknik kullanılmaz.
- Krom ve Alüminyum detay ile zerafet ve estetik bir görünüm yakalanır.
- Kanatlarımızın içine sıvı poliüretan enjekte edilip, 300 tonluk preslerde sertleştirilerek 42 dansite yoğunlukta poliüretan dolgu malzemesi ile Kanatlarımız güçlendirilir. Böylece 40 ton darbeye 15 ton eğilme direnci gibi muhteşem bir mukavemete kavuşur. Ayrıca poliüretan ile kapı kanadı içinden yüksek ses ve ısı izolasyonu sağlandığı gibi korozyona dayanıklı ve anti bakteriyel bir kapı kanadı elde etmemizi sağlar.
- Merkezi 14 lü kilit sistemi, gizli emniyet kelepçesi ve menteşe tarafında 6 adet sabit emniyet pimi ile kapı güvenliği güçlendirilir.
- Kapılarda aksesuarlar olarak zengin bir yelpazeye sahiptir kanat üzerindeki geniş açılı lüks dürbün ile kapı arkasını rahatlık ve güven içinde kontrol etmenizi sağlayacak şekilde tasarlanmıştır.
- Üründe kullanılan paslanmaz lüks çekme kolu, iç açma kolu ve kanat etrafı parlak eloksallı alüminyum kanat kısmına ayrı bir estetik kazandırırken kaynaksız ayarlı menteşelerle kapınızın rahat ve ergonomik hareketini sağlamaktadır.

KAPI KASALARIMIZ

- 2mm çelik den üretilmiş olup 18 -24 cm duvar kalınlığına standart ölçülerde ayarlı kasa olarak tasarlanmıştır. Ayrıca opsiyonel extra olarak 24 cm üzeri olan ölçülerde, yarım kasa, sabit kasa ve profil kasa sistemleride özel üretim olarak hazırlanabilir. Tüm delik ve kesimler CNC makine parkımızda estetik ve seri imalatı yapılır. Gaz altı kaynak ve özel birleştirme tezgahlarımızda toplanmak tadır. Kasalarımız standart üretimde elektrostatik toz boya uygulanmış olarak satışa sunulur.

OPSİYONEL

Alüminyum yada Ahşap kasa kaplama seçeneği bulunmaktadır.

OUR DOOR LEAF

- 1.2mm x 2 monolithic galvanized steel plate is manufactured with The help of our CNC machines which also ensures pressing, bending and mashing. Part steel or welding etc. no debilitating techniques used.
- Elegance and aesthetic appearance are captured with chrome and aluminum detail.
- Liquid is injected into our leaf and hardened in presses of 300 tons to strengthen our leaves with polyurethane filling material at 42 density. Thus, 40 tons of blows and 15 tons of bending resistance as well as a magnificent power. We also provide high sound and heat insulation, corrosion resistance and anti bacterial door leaf from our door with polyurethane.
- Central 14 locking system, hidden safety clamp and 6 fixed on the hinge side. With the safety pin, door security is strengthened.
- As door accessories; with the peephole on door sash, so that you can comfortably and safely control the back of the door. The luxurious stainless pulling handle, the inner stainless opening handle and the brilliant anodized aluminum around the sash give a distinct esthetic to the wing, the adjustable hinges provide the comfortable and ergonomic movement of your door.

OUR DOOR FRAMES

- 18 -24 cm wall thickness standard size adjustable case are produced and designed from 2mm galvanized steel sheets. Above 24 cm dimensions an optional extra steel piece will be added, in the system of half-frame, fixed case and profile case can be prepared as a special production. All holes and cuts are made in our CNC machines esthetically. We are assembling with inert-gas welding and special joining machines. We are selling our products with electrostatic powder paint In standard production.

OPTIONAL

Aluminum or Wooden frame coverin

ASYMMETRIC



Asymmetric

KASA

- 2 mm galvaniz çelik
- 18 - 24 cm duvar kalınlığı
- 24 cm ve üzeri özel ölçü
- Standart elektrostatik toz boya
- Kasa içi dekoratif eloksallı alüminyum profil

OPSİYONEL

- Alüminyum & Ahşap kasa kaplama seçeneği

KANAT

- 1,2 mm X 2 yekpare galvaniz çelik
- Çelik üzeri 6 mm temperli dekoratif cam yüzey
- 42 densite poliüretan dolgu
- Kancalı kilit sistemi
- 3 adet sabit emniyet pimi
- Gizli emniyet kelepçesi
- 120 cm Krom yada alüminyum kare kol
- Kanat etrafı dekoratif eloksallı alüminyum çıta
- Geniş açılı lüks dürbün
- Kaynaksız ayarlı menteşe

DOOR FRAME

- It is made from 2 mm galvanized steel
- Frame can be adjusted to 18 cm - 24 cm wall thickness
- Over 24 cm holds special manufacturing
- Electrostatic powder paint
- Inside frame has decorative eloxal aluminium profile

OPTIONAL

- Wooden or aluminium frame coating can be done (Optional)

DOOR LEAF

- It is made from 1,2 mm two monolith plates galvanized steel
- Decorative designed 6mm tempered glass fitten surface over front steel leaf
- Inside door leaf is filled by 42 density polyurethane
- Hook locking system
- 3 pieces stable safety pin
- Hidden safety clips
- Chromium or aluminium quadratic 120 cm door handle
- Luxury peephole
- Weldless adjustable hinges
- Around door leaf is designed by special anodized aluminium

FLZ 119

Asimetrik Seri
Asymmetric Series



Dış Cephe için uygun Düneşe Dayanıklı Yüzey

Suitable For Exterior Faced



Darbeye Dayanır 40 Ton

Impact Resistant 40 Tonne



Eğilmeye Dayanır 5 Ton

Flexure Endurance 5 Tonne



Ayarlı Menteşe

Adjustable Hinge



Dış Cephe için uygundur. Neme Dayanır

Suitable For Exterior Moisture Resistant



Dayanıklı Ön Zırh

Durable Shield



Ses İzolasyonu Sağlar

Sound Insulation



Isı İzolasyonu Sağlar

Cold Proof Thermal Insulation



Çevre Dostudur

Eco-Friendly



Yangına Karşı Dayanır

Fire Resistant



Çizilmeye Karşı Dayanır

Resistance To Scratching



FLZ 118

Asimetrik Seri
Asymmetric Series

Asymmetric

KASA

- 2 mm galvaniz çelik
- 18 - 24 cm duvar kalınlığı
- 24 cm ve üzeri özel ölçü
- Standart elektrostatik toz boya
- Kasa içi dekoratif eloksallı alüminyum profil

OPSİYONEL

- Alüminyum & Ahşap kasa kaplama seçeneği

KANAT

- 1,2 mm X 2 yekpare galvaniz çelik
- Çelik üzeri 6 mm temperli dekoratif cam yüzey
- 42 densite poliüretan dolgu
- Kancalı kilit sistemi
- 3 adet sabit emniyet pimi
- Gizli emniyet kelepçesi
- 120 cm Krom yada alüminyum kare kol
- Kanat etrafı dekoratif eloksallı alüminyum çita
- Geniş açılı lüks dürbün
- Kaynaksız ayarlı menteşe

DOOR FRAME

- It is made from 2 mm galvanized steel
- Frame can be adjusted to 18 cm - 24 cm wall thickness
- Over 24 cm holds special manufacturing
- Electrostatic powder paint
- Inside frame has decorative eloxal aluminium profile

OPTIONAL

- Wooden or aluminium frame coating can be done (Optional)

DOOR LEAF

- It is made from 1,2 mm two monolith plates galvanized steel
- Decorative designed 6mm tempered glass fitten surface over front steel leaf
- Inside door leaf is filled by 42 density polyurethane
- Hook locking system
- 3 pieces stable safety pin
- Hidden safety clips
- Chromium or aluminium quadratic 120 cm door handle
- Luxury peephole
- Weldless adjustable hinges
- Around door leaf is designed by special anodized aluminium



ASYMMETRIC

ASYMMETRIC



FLZ 118

Asimetrik Seri
Asymmetric Series

Asymmetric

KASA

- 2 mm galvaniz çelik
- 18 - 24 cm duvar kalınlığı
- 24 cm ve üzeri özel ölçü
- Standart elektrostatik toz boya
- Kasa içi dekoratif eloksallı alüminyum profil

OPSİYONEL

- Alüminyum & Ahşap kasa kaplama seçeneği

KANAT

- 1,2 mm X 2 yekpare galvaniz çelik
- Çelik üzeri özel modellenli MDF yüzey
- 42 densite poliüretan dolgu
- Kanca kilit sistemi
- 3 adet sabit emniyet pimi
- Gizli emniyet kelepçesi
- 30 cm Krom yada alüminyum kare kol
- Kanat etrafı dekoratif eloksallı alüminyum çıta
- Geniş açılı lüks dürbün
- Kaynaksız ayarlı menteşe

DOOR FRAME

- It is made from 2 mm galvanized steel
- Frame can be adjusted to 18 cm - 24 cm wall thickness
- Over 24 cm holds special manufacturing
- Electrostatic powder paint
- Inside frame has decorative eloxal aluminium profile

OPTIONAL

- Wooden or aluminium frame coating can be done (Optional)

DOOR LEAF

- It is made from 1,2 mm two monolith plates galvanized steel
- Special modelling natural MDF coating over steel surface
- Inside door leaf is filled by 42 density polyurethane
- Hook locking system
- 6 pieces stable safety pin
- Hidden safety clips
- Chromium or aluminium quadratic 120 cm door handle
- Luxury peephole
- Weldless adjustable hinges
- Around door leaf is designed by special anodized aluminium



Darbeye Dayanır
40 Ton

Impact
Resistant
40 Tonne



Eğilmeye
Dayanır
5 Ton

Flexure
Endurance
5 Tonne



Ayarlı
Menteşe

Adjustable
Hinge



Dayanıklı
Ön Zırh

Durable
Shield



Ses İzolasyonu
Sağlar

Sound
Insulation



Isı İzolasyonu
Sağlar

Cold Proof
Thermal
Insulation



Çevre Dostudur

Eco-Friendly



Yangına Karşı
Dayanır

Fire Resistant



Çizilmeye Karşı
Dayanır

Resistance To
Scratching



FLZ 119

Asimetrik Seri
Asymmetric Series

Asymmetric

KASA

- 2 mm galvaniz çelik
- 18 - 24 cm duvar kalınlığı
- 24 cm ve üzeri özel ölçü
- Standart elektrostatik toz boya
- Kasa içi dekoratif eloksallı alüminyum profil

OPSİYONEL

- Alüminyum & Ahşap kasa kaplama seçeneği

KANAT

- 1,2 mm X 2 yekpare galvaniz çelik
- Çelik üzeri özel modellenli MDF yüzey
- 42 densite poliüretan dolgu
- Kanca kilit sistemi
- 3 adet sabit emniyet pimi
- Gizli emniyet kelepçesi
- 30 cm Krom yada alüminyum kare kol
- Kanat etrafı dekoratif eloksallı alüminyum çıta
- Geniş açılı lüks dürbün
- Kaynaksız ayarlı menteşe

DOOR FRAME

- It is made from 2 mm galvanized steel
- Frame can be adjusted to 18 cm - 24 cm wall thickness
- Over 24 cm holds special manufacturing
- Electrostatic powder paint
- Inside frame has decorative eloxal aluminium profile

OPTIONAL

- Wooden or aluminium frame coating can be done (Optional)

DOOR LEAF

- It is made from 1,2 mm two monolith plates galvanized steel
- Special modelling natural MDF coating over steel surface
- Inside door leaf is filled by 42 density polyurethane
- Hook locking system
- 6 pieces stable safety pin
- Hidden safety clips
- Chromium or aluminium quadratic 120 cm door handle
- Luxury peephole
- Weldless adjustable hinges
- Around door leaf is designed by special anodized aluminium



Darbeye Dayanır
40 Ton



Flexure
Endurance
5 Tonne



Ayarlı
Menteşe



Dayanıklı
Ön Zırh



Ses İzolasyonu
Sağlar



Isı İzolasyonu
Sağlar



Çevre Dostudur



Yangına Karşı
Dayanır



Çizilmeye Karşı
Dayanır



Resistance To
Scratching